

All Flange Tee (Class K14)

Nominal Bore		Dimensions				Weight	
Body	Branch	Series A		Series B		Epoxy	Lined
mm	mm	L mm	H mm	L mm	H mm	Kgs.	Kgs.
50	50	300	150	-	-	13	13
80	50	330	160	-	-	14	14
80	80	330	165	-	-	16	16
100	50	360	170	-	-	17	18
100	80	360	175	330	170	18	19
100	100	360	180	-	-	19	20
125	50	400	185	-	-	20	21
125	80	400	190	-	-	22	23
125	125	400	200	-	-	25	26
150	50	440	200	-	-	29	30
150	80	440	205	360	200	30	31
150	100	440	210	380	205	31	32
150	125	440	215	-	-	34	35
150	150	440	220	-	-	34	35
200	80	520	235	380	225	40	42
200	100	520	240	400	230	41	43
200	150	520	250	460	245	44	46
200	200	520	260	-	-	49	52
250	80	700	265	405	265	65	69
250	100	700	275	425	270	67	71
250	150	700	300	485	280	70	74
250	200	700	325	540	290	75	80
250	250	700	350	600	300	87	91
300	80	800	290	425	295	91	97
300	100	800	300	450	300	93	99
300	150	800	325	505	310	96	102
300	200	800	350	565	320	101	107
300	250	800	375	620	330	108	114
300	300	800	400	680	340	117	124
350	80	850	325	-	-	131	140
350	150	850	325	-	-	135	143
350	300	850	425	-	-	158	144
350	350	850	425	-	-	167	173
400	80	900	350	-	-	166	172
400	100	900	350	-	-	168	174
400	150	900	350	-	-	155	169
400	200	900	350	-	-	159	173
400	250	900	350	-	-	161	175
400	300	900	450	-	-	177	191
400	400	900	450	-	-	194	210
450	80	950	375	-	-	187	203
450	100	950	375	-	-	188	204
450	150	950	375	-	-	190	206
450	200	950	375	-	-	193	209
450	300	950	475	-	-	213	230
450	350	950	475	-	-	221	239
450	400	950	475	-	-	229	248

Nominal Bore		Dimensions				Weight	
Body	Branch	Series A		Series B		Epoxy	Lined
mm	mm	L mm	H mm	L mm	H mm	Kgs.	Kgs.
450	450	950	475	-	-	237	257
500	80	1000	400	-	-	237	255
500	100	1000	400	-	-	241	259
500	150	1000	400	-	-	241	259
500	200	1000	400	-	-	245	264
500	300	1000	500	-	-	279	258
500	500	1000	500	-	-	304	325
600	150	1100	450	-	-	379	398
600	200	1100	450	-	-	380	399
600	300	1100	550	-	-	369	396
600	450	1100	550	-	-	404	431
600	500	1100	550	-	-	408	425
600	600	1100	550	-	-	491	519
700	400	870	555	-	-	381	409
700	700	1200	600	-	-	548	589
800	400	910	615	-	-	472	512
800	600	1350	645	-	-	699	749
800	800	1350	675	-	-	741	794
900	400	950	675	-	-	578	630
900	600	1500	705	-	-	900	960
900	900	1500	750	-	-	974	1040
1000	400	990	735	-	-	732	791
1000	600	1650	765	-	-	1112	1182
1000	1000	1650	825	-	-	1290	1370
1200	600	1250	885	-	-	1259	1328
1200	1200	1950	975	-	-	2055	2169
1400	600	1550	980	-	-	1692	1823
1400	1200	1750	1025	-	-	2534	2624
1600	600	1450	1125	-	-	2240	2395
1600	1200	2300	1180	-	-	3238	3328

