

Double Socket Tapers (Class K12)

Tapering		Dimensions	Weight	
From	To		Epoxy	Lined
mm	mm	L mm	Kgs.	Kgs.
100	80	85	7	8
150	80	190	10	11
150	100	150	10	11
200	100	250	15	17
200	150	145	16	17
250	100	250	21	23
250	150	250	23	25
250	200	150	22	24
300	150	370	31	34
300	200	250	33	35
300	250	150	34	36
350	200	370	46	50
350	250	260	43	47
350	300	160	42	45
400	200	360	57	62
400	250	360	60	65
400	300	260	63	67
400	350	160	52	56
450	250	260	77	83
450	300	260	79	85
450	350	260	79	85
450	400	160	69	73
500	250	360	97	105
500	300	360	95	103
500	350	360	89	97
500	400	260	84	92
500	450	160	78	84
600	300	460	145	155
600	350	460	148	148
600	400	460	132	142
600	450	360	124	134
600	500	260	116	126
700	500	480	215	227
700	600	280	193	203
800	600	480	270	284
800	700	280	277	289
900	700	480	379	401
900	800	280	355	365
1000	800	480	475	487
1000	900	280	446	458
1200	1000	480	716	731
1200	1100	360	693	709
1400	1200	360	949	964
1600	1400	360	1288	1308

